

# MF3Dx2 v2

## Security Target Lite

Rev. 1.1 — 17 January 2019

NSCIB-CC-207017

Evaluation document

### Document information

Information	Content
Keywords	Common Criteria, Security Target Lite, MF3Dx2 v2 with IC Dedicated Support Software
Abstract	Evaluation of the MF3Dx2 v2 developed and provided by NXP Semiconductors, Business Unit Security and Connectivity, according to the Common Criteria for Information Technology Evaluation Version 3.1 at EAL5 augmented



## Revision History

Rev.	Date	Description
1.1	2019-01-17	Derived from Security Target v1.2

## 1 Introduction

### 1.1 ST Reference

MF3Dx2 v2 Security Target Lite, Version 1.1, NXP Semiconductors, 17 January 2019.

### 1.2 TOE Reference

NXP Secure Smart Card Controller MF3Dx2 v2.

### 1.3 TOE Overview

NXP has developed the MF3Dx2 v2 to be used with Proximity Coupling Devices (PCDs, also called "terminal") according to ISO 14443 Type A. The communication protocol complies to part ISO 14443-4. The MF3Dx2 v2 is primarily designed for secure contactless transport applications and related loyalty programs as well as access control systems as well as closed loop payment systems. It fully complies with the requirements for fast and highly secure data transmission, flexible memory organisation and interoperability with existing infrastructure.

The TOE is a smart card comprising a hardware platform and a fixed software package. The software package is stored in Flash and ROM memory and provides an operating system with a set of functions, used to manage the various kinds of data files stored in Flash memory. The operating system supports a separation between the data of different applications and provides access control if required by the configuration.

The TOE includes also IC Dedicated Software to support its start-up and for test purposes after production. The Smart Card Controller hardware comprises an 16-bit CPU, volatile and non-volatile memories, cryptographic co-processors, security components and one communication interface.

The TOE includes a functional specification and a guidance document. This documentation contains a description of the hardware and software interface, the secure configuration and usage of the product by the terminal designer.

The security measures of the TOE are designed to act as an integral part of the combination of hardware platform and software package in order to strengthen the product as a whole. Several security measures are completely implemented in and controlled by the hardware. Other security measures are controlled by the combination of hardware and software or software guided exceptions.

#### 1.3.1 Required non-TOE Hardware/Software/Firmware

The TOE requires an ISO 14443 card terminal to be provided with power and to receive adequate commands.

### 1.4 TOE Description

#### 1.4.1 Physical Scope of the TOE

The Target of Evaluation (TOE) is the smartcard integrated circuit named MF3Dx2 v2 in combination with a fixed software package, the IC Dedicated Software. The TOE includes IC manufacturer proprietary IC Dedicated Test Software and IC Dedicated

Support Software, according to the terminology used in the Security IC Protection Profile [6].

**Table 1. TOE deliverables**

Type	Name	Release	Form of delivery
IC Hardware	MF3Dx2 v2 Hardware	22.0	Sawn wafer (FFC), modules (MOB4, MOB6)
IC Dedicated Test Software	Test Software	9.2.3	On-chip software
IC Dedicated Support Software	Boot Software	9.2.3	On-chip software
	Firmware	9.2.3	On-chip software
	MIFARE DESFire Software	2.2	On-chip software
Document	MF3Dx2 v2, Information on Guidance and Operation, Guidance and Operation Manual [9]	1.3	Electronic document (PDF via NXP DocStore)

In addition to the deliverables listed above, a datasheet is provided. The reference is provided in the following two tables, where depending on the memory size, a separate manual is delivered:

**Table 2. Datasheet for 2, 4 and 8 KB memory sizes**

Type	Name	Release	Form of delivery
Document	MF3Dx200Dpp(p)/02, MIFARE DESFire EV2 contactless smartcard IC, Objective data sheet [7]	1.1	Electronic document (PDF via NXP DocStore)

**Table 3. Datasheet for 16 and 32 KB memory sizes**

Type	Name	Release	Form of delivery
Document	MF3D92/MF3DA2, MIFARE DESFire EV2 16KB and 32KB contactless smartcard IC, Objective data sheet [8]	1.1	Electronic document (PDF via NXP DocStore)

The TOE (hardware) is shipped to the customer by NXP. The available documentation can be downloaded by customers in PDF format directly from the NXP DocStore.

The customer can check the version of the IC Hardware and IC Dedicated Software by using the GetVersion APDU as described in Chapter 3.1 of the UGM [9]. Additionally, the originality of the TOE can be determined by authentication with an Originality Key, as described in Chapter 3.2 of the UGM [9].

#### 1.4.1.1 Available Memory Sizes

The TOE is available in various memory sizes. Each memory size has a different commercial type name. A commercial type name for the TOE starts with the following general format:

- MF3D(H)x2

The letter 'H' in the commercial type name is optional and is therefore listed above in parentheses. It is used to identify an input capacitance of 70 pF when the letter is used,

compared to 17 pF when the letter is not used. The letter 'x' is a placeholder for the selected memory size. The following table lists the available options:

**Table 4. Available memory sizes**

Identifier	Description	Assignment	Meaning
x	memory size	2	2 KB of memory available
		4	4 KB of memory available
		8	8 KB of memory available
		9	16 KB of memory available
		A	32 KB of memory available

All commercial type names are subject to this evaluation. However the identifier "MF3Dx2" will be used in the remainder of this document to make referencing easier. All information and security functionality described in this Security Target applies to all commercial types.

**1.4.2 Logical Scope of the TOE**

**1.4.2.1 Hardware Description**

The CPU of the MF3Dx2 v2 has an 16-bit architecture. The on-chip hardware components are controlled by the MIFARE DESFire Software via Special Function Registers. These registers are correlated to the activities of the CPU, the memory management unit, interrupt control, contactless communication, Flash, timers, the DES co-processor and the AES co-processor. The communication with the MF3Dx2 v2 can be performed through the contactless interface.

The Triple-DES coprocessor supports Triple-DES operations with key lengths of 112 bits and 168 bits. The AES coprocessor supports AES operations with three different key lengths of 128, 192 or 256 bit.

A hardware Random Number Generator provides true random numbers which are used to seed deterministic random number generators, used internally by the DESFire functionality for security purposes.

**1.4.2.2 Software Description**

The IC Dedicated Test Software (Test ROM Software) located in ROM of the TOE is used by the TOE Manufacturer to test the functionality of the chip. The test functionality is disabled before the operational use of the smart card. The IC Dedicated Test Software includes the test operating system, test routines for the various blocks of the circuitry and shutdown functions to ensure that security relevant test operations cannot be executed illegally after phase 3 of the TOE Life cycle.

The TOE also contains IC Dedicated Support Software. The Boot Software which is stored in ROM is part of the IC Dedicated Support Software. This software is executed after each reset of the TOE, i.e. every time when the TOE starts. It sets up the TOE and does some basic configuration. The MIFARE DESFire Software is also part of the IC Dedicated Support Software and provides the main functionality of the TOE in the usage phase. The MF3Dx2 v2 is primarily designed for secure contactless transport applications and related loyalty programs as well as access control systems. It fully complies with the requirements for fast and highly secure data transmission, flexible memory organization and interoperability with existing infrastructure. Its functionality consists of:

- Flexible file system that groups user data into applications and files within each application.
- Support for different file types like values or data records.
- Mutual three pass authentication, also according to ISO 7816-4.
- Authentication on application level with fine-grained access conditions for files.
- Multi-application support that allows distributed management of applications and ensures application segregation.
- Delegated-application support that allows third party service providers to create their applications onto the issued TOE.
- Multiple application selection that allows transaction over files in two applications.
- Data encryption on the communication path.
- Message Authentication Codes (MAC) for replay attack protection.
- Transaction system with rollback that ensures consistency for complex transactions.
- Unique serial number for each device (UID) with optional random UID.
- Key set rolling feature per application to switch to a predefined key set.
- Transaction MAC feature to prevent fraudulent merchant attacks.
- Originality functionality that allows verifying the authenticity of the TOE.
- Virtual Card architecture to allow multiple applications on one device.
- Proximity check feature against relay attacks on the TOE.
- MIFARE DESFire D40 backward compatible mode for authentication.
- MIFARE DESFire EV1 backward compatible mode for authentication.

The TOE features enable it to be used for a variety of applications:

- Electronic fare collection.
- Stored value card systems.
- Access control systems.
- Loyalty.

If privacy is an issue, the TOE can be configured not to disclose any information to unauthorized users.

#### 1.4.2.3 Documentation

The Product Data Sheet [\[7\]](#) contains a functional description of the communication protocol and the commands implemented by the TOE. The provided documentation can be used by a customer to develop applications using the TOE.

The Product Data Sheet is supported by a User Guidance Manual [\[9\]](#) which gives additional guidance with regards to the secure usage of the TOE.

#### 1.4.3 Life Cycle and Delivery of the TOE

The life-cycle phases are organized according to the Security IC Platform Protection Profile with Augmentation Packages [\[6\]](#), Section 1.2.4:

- Phase 1: IC Embedded Software Development
- Phase 2: IC Development
- Phase 3: IC Manufacturing
- Phase 4: IC Packaging
- Phase 5: Composite Product Integration
- Phase 6: Personalisation
- Phase 7: Operational Usage

For the usage phase the MF3Dx2 v2 chip will be embedded in a credit card (meaning ID-1 sized) plastic card (micro-module embedded into the plastic card) or another sealed package. The module and card embedding of the TOE provide external security mechanisms because they make it harder for an attacker to access parts of the TOE for physical manipulation.

Regarding the Application Note 1 of the Protection Profile [6], NXP will deliver the TOE at the end of Phase 3 in form of wafers or at the end of Phase 4 in packaged form. Therefore the TOE evaluation perimeter comprising the development and production environment of the TOE, consists of life-cycle phases 2 - 4 (according to the Protection Profile [6], Section 1.2.4).

Regarding the Application Note 2 of the Protection Profile [6], the TOE provides additional functionality which is not covered in the Protection Profile. The additional functionality is due to the MIFARE DESFire Software that is part of the IC Dedicated Support Software and included in this evaluation. The MIFARE DESFire Software is embedded in the TOE during the TOE evaluation perimeter (life-cycle phases 2 - 4) and the TOE does not allow the application of any IC Embedded Software after TOE delivery. Moreover, the TOE is getting locked before TOE delivery at the end of Phase 3 or Phase 4.

The TOE is able to control two different logical phases. After production of the chip every start-up will lead to the Test Mode and the execution of the IC Dedicated Test Software. At the end of the production test the access to the IC Dedicated Test Software is disabled. With disabled test software every start-up of the chip will lead to the User Mode with the CPU executing the MIFARE DESFire Software.

#### 1.4.4 TOE Intended Usage

The TOE user environment is the environment from TOE Delivery to Phase 7. At the phases up to 6, the TOE user environment must be a controlled environment. Regarding to Phase 7, the TOE is used by the end-user. The method of use of the product in this phase depends on the application. The TOE is intended to be used in an unsecured environment that does not avoid a threat.

The device is developed for high-end safeguarded applications, and is designed for embedding into contact-less smart cards according to ISO 14443. Usually the smart card is assigned to a single individual only and the smart card may be used for multiple applications in a multi-provider environment. The secret data shall be used as input for the calculation of authentication data, encryption and integrity protection of data for communication.

In the end-user environment (Phase 7) smart card ICs are used in a wide range of applications to assure authorized conditional access. Examples of such are transportation or access management. The end-user environment therefore covers a wide spectrum of very different functions, thus making it difficult to avoid and monitor any abuse of the TOE.

The system integrators such as the terminal software developer may use samples of the TOE during the development phases for their testing purposes. These samples do not differ from the TOE, they do not have any additional functionality used for testing.

#### 1.4.5 Interface of the TOE

The electrical interface of the TOE are the pads to connect the RF antenna, which allows communication according to ISO 14443 Type A. The communication protocol complies to

part ISO 14443-4. The functional interface is defined by the commands implemented by the TOE and described in the product data sheet.

The chip surface can be seen as an interface of the TOE, too. This interface must be taken into account regarding environmental stress e.g. like temperature and in the case of an attack where the attacker e.g. manipulates the chip surface.



## 2 Conformance Claims

### 2.1 CC Conformance Claim

This Security Target claims to be conformant to the Common Criteria version 3.1:

- Common Criteria for Information Technology Security Evaluation, Part 1: Introduction and general model, Version 3.1, Revision 5, CCMB-2017-04-001, April 2017 [2].
- Common Criteria for Information Technology Security Evaluation, Part 2: Security functional components, Version 3.1, Revision 5, CCMB-2017-04-002, April 2017 [3].
- Common Criteria for Information Technology Security Evaluation, Part 3: Security assurance components, Version 3.1, Revision 5, CCMB-2017-04-003, April 2017 [4].

For the evaluation the following methodology will be used:

- Common Methodology for Information Technology Security Evaluation, Evaluation methodology, Version 3.1, Revision 5, CCMB-2017-04-004, April 2017 [5].

This Security Target claims to be CC Part 2 extended and CC Part 3 conformant. The extended Security Functional Requirements are defined in [Section 5](#).

### 2.2 PP Claim

This Security Target claims strict conformance to the following Protection Profile:

- Security IC Platform Protection Profile with Augmentation Packages, Registered and Certified by Bundesamt für Sicherheit in der Informationstechnik (BSI) under the reference BSI-CC-PP-0084-2014, Version 1.0, 13 January 2014 [6].

### 2.3 Package Claim

This Security Target claims conformance to the assurance package EAL5 augmented with AVA\_VAN.5 and ALC\_DVS.2.

### 2.4 Conformance Claim Rationale

As the Protection Profile [6] requires strict conformance, no conformance claim requirement is needed in this Security Target.

### 3 Security Problem Definition

This section lists the assets, threats, organisational security policies and assumptions from the Protection Profile [6] and describes extensions to these elements in detail.

#### 3.1 Description of Assets

The assets to be protected (related to standard functionality) are described in Section 3.1 of the Protection Profile [6] and are listed below:

- The user data of the Composite TOE.
- The Security IC Embedded Software, stored and in operation.
- The security services provided by the TOE for the Security IC Embedded Software.

These assets are related to the following high-level security concerns:

- Integrity of user data of the Composite TOE.
- Confidentiality of user data of the Composite TOE being stored in the TOE’s protected memory areas.
- Correct operation of the security services provided by the TOE for the Security IC Embedded Software.
- Deficiency of random numbers.

To be able to protect these assets the TOE shall self-protect its security functionality. Critical information about the security functionality shall be protected by the development environment and the operational environment. Critical information may include:

- Logical design data, physical design data, IC Dedicated Software, and configuration data.
- Initialisation Data and Pre-personalisation Data, specific development aids, test and characterisation related data, material for software development support, and photomasks.

For details see Section 3.1 of the Protection Profile [6].

#### 3.2 Threats

All threats for the TOE which are defined in section 3.2 of the Protection Profile are applied to this Security Target and are listed in Table 5.

**Table 5. Threats defined in the Protection Profile (PP-0084)**

Name	Title
T.Leak-Inherent	Inherent Information Leakage
T.Phys-Probing	Physical Probing
T.Malfunction	Malfunction due to Environmental Stress
T.Phys-Manipulation	Physical Manipulation
T.Leak-Forced	Forced Information Leakage
T.Abuse-Func	Abuse of Functionality
T.RND	Deficiency of Random Numbers

For details see Section 3.2 of the Protection Profile [6].

The following additional threats are defined in this Security Target:

**Table 6. Additional threats defined in this Security Target**

Name	Title
T.Data-Modification	Unauthorised Data Modification
T.Impersonate	Impersonating authorised users during authentication
T.Cloning	Cloning

**T.Data-Modification**

**Unauthorised Data Modification**

User data stored by the TOE may be modified by unauthorised subjects. This threat applies to the processing of modification commands received by the TOE, it is not concerned with verification of authenticity.

**T.Impersonate**

**Impersonating authorised users during authentication**

An unauthorised subject may try to impersonate an authorised subject during the authentication sequence, e.g. by a man-in-the-middle or replay attack.

**T.Cloning**

**Cloning**

User and TSF data stored on the TOE (including keys) may be read out by an unauthorised subject in order to create a duplicate.

### 3.3 Organisational Security Policies

All organisational security policies defined in the Protection Profile are valid for this Security Target and are listed in [Table 7](#). For details see Section 3.3 of the Protection Profile [\[6\]](#).

**Table 7. Organisational security policies defined in the Protection Profile (PP-0084)**

Name	Title
P.Process-TOE	Identification during TOE Development and Production

This Security Target defines additional organisational security policies as detailed in the following.

The TOE provides specific security functionality which can be used by the MIFARE DESFire software. In the following specific security functionality is listed which is not derived from threats identified for the TOE's environment because it can only be decided in the context of the smart card application against which threats the MIFARE DESFire software will use the specific security functionality.

The IC Developer / Manufacturer therefore applies the policies 'Confidentiality during communication', 'Integrity during communication', 'Transaction mechanism' and 'Untraceability of end-users' as specified below.

**Table 8. Additional organisational security policies defined in this Security Target**

Name	Title
P.Encryption	Confidentiality during communication

Name	Title
P.MAC	Integrity during communication
P.Transaction	Transaction mechanism
P.No-Trace	Untraceability of end-users

<b>P.Encryption</b>	<p><b>Confidentiality during communication</b></p> <p>The TOE shall provide the possibility to protect selected data elements from eavesdropping during contactless communication.</p>
<b>P.MAC</b>	<p><b>Integrity during communication</b></p> <p>The TOE shall provide the possibility to protect the contactless communication from modification or injections. This includes especially the possibility to detect replay or man-in-the-middle attacks within a session.</p>
<b>P.Transaction</b>	<p><b>Transaction mechanism</b></p> <p>The TOE shall provide the possibility to combine a number of data modification operations in one transaction, so that either all operations or no operation at all is performed.</p>
<b>P.No-Trace</b>	<p><b>Untraceability of end-users</b></p> <p>The TOE shall provide the ability that authorised subjects can prevent that end-user of TOE may be traced by unauthorised subjects without consent. Tracing of end-users may happen by performing a contactless communication with the TOE when the end-user is not aware of it. Typically this involves retrieving the UID or any freely accessible data element.</p>

### 3.4 Assumptions

All assumptions defined in the Protection Profile are valid for this Security Target and are listed in [Table 9](#). For details see Section 3.4 of the Protection Profile [\[6\]](#).

**Table 9. Assumptions defined in the Protection Profile (PP-0084)**

Name	Title
A.Process-Sec-IC	Protection during Packaging, Finishing and Personalisation
A.Resp-Appl	Treatment of user data of the Composite TOE

In compliance with Application Notes 6 and 7 in the Protection Profile [\[6\]](#), this Security Target defines two additional assumptions as follows:

**Table 10. Additional assumptions defined in this Security Target**

Name	Title
A.Secure-Values	Usage of secure values
A.Terminal-Support	Terminal Support

**A.Secure-Values****Usage of secure values**

Only confidential and secure cryptographically strong keys shall be used to set up the authentication. These values are generated outside the TOE and they are downloaded to the TOE.

**A.Terminal-Support****Terminal Support**

The terminal verifies information sent by the TOE in order to ensure integrity and confidentiality of the communication. Furthermore the terminal shall provide random numbers according to AIS20 or AIS31 for the authentication.

The additional assumptions as defined above are required for the correct functioning of the DESFire security functionality. As the Protection Profile [6] does not cover this kind of functionality, the additional assumptions neither mitigate a threat (or a part of a threat) meant to be addressed by security objectives for the TOE in the Protection Profile [6], nor fulfil an OSP (or part of an OSP) meant to be addressed by security objectives for the TOE in the Protection Profile [6].

## 4 Security Objectives

### 4.1 Security Objectives for the TOE

All security objectives for the TOE which are defined in section 4.1 of the Protection Profile are applied to this Security Target and are listed in [Table 11](#).

**Table 11. Security Objectives of the TOE (PP-0084)**

Name	Title
O.Leak-Inherent	Protection against Inherent Information Leakage
O.Phys-Probing	Protection against Physical Probing
O.Malfunction	Protection against Malfunctions
O.Phys-Manipulation	Protection against Physical Manipulation
O.Leak-Forced	Protection against Forced Information Leakage
O.Abuse-Func	Protection against Abuse of Functionality
O.Identification	TOE Identification
O.RND	Random Numbers

Regarding the Application Notes 8 and 9 in the Protection Profile [6](#), additional security objectives that are based on additional functionality provided by the TOE are defined below:

**Table 12. Additional security objectives defined in this Security Target**

Name	Title
O.Access-Control	Access Control
O.Authentication	Authentication
O.Encryption	Confidential Communication
O.MAC	Integrity-Protected Communication
O.No-Trace	Preventing Traceability
O.Transaction	Transaction Mechanism
O.Type-Consistency	Data Type Consistency

#### **O.Access-Control**

#### **Access Control**

The TOE must provide an access control mechanism for data stored by it. The access control mechanism shall apply to read, modify, create and delete operations for data elements and to reading and modifying security attributes as well as authentication data. It shall be possible to limit the right to perform a specific operation to a specific user. The security attributes (keys) used for authentication shall never be output.

#### **O.Authentication**

#### **Authentication**

The TOE must provide an authentication mechanism in order to be able to authenticate authorised users. The

authentication mechanism shall be resistant against replay and man-in-the-middle attacks.

**O.Encryption**

**Confidential Communication**

The TOE must be able to protect the communication by encryption. This shall be implemented by security attributes that enforce encrypted communication for the respective data elements.

**O.MAC**

**Integrity-Protected Communication**

The TOE must be able to protect the communication by adding a MAC. This shall be implemented by security attributes that enforce integrity protected communication for the respective data elements. Usage of the protected communication shall also support the detection of injected and bogus commands within the communication session before the protected data transfer.

**O.No-Trace**

**Preventing Traceability**

The TOE must be able to prevent that the TOE end-user can be traced. This shall be done by providing an option that disables the transfer of privacy-related information that is suitable for tracing an end-user by an unauthorised subject.

**O.Transaction**

**Transaction Mechanism**

The TOE must be able to provide a transaction mechanism that allows to update multiple data elements either all in common or none of them.

**O.Type-Consistency**

**Data Type Consistency**

The TOE must provide a consistent handling of the different supported data types. This comprises over- and underflow checking for values, for data file sizes and record handling.

**4.2 Security Objectives for the Security IC Embedded Software**

All security objectives for the Security IC Embedded Software which are defined in section 4.2 of the Protection Profile are applied to this Security Target and are listed in [Table 13](#).

**Table 13. Security Objectives for the Security IC Embedded Software (PP-0084)**

Name	Title
OE.Resp-Appl	Treatment of User Data

**4.3 Security Objectives for the Operational Environment**

All security objectives for the operational environment which are defined in section 4.3 of the Protection Profile are applied to this Security Target and are listed in [Table 14](#).

**Table 14. Security Objectives for the Operational Environment (PP-0084)**

Name	Title
OE.Process-Sec-IC	Protection during composite product manufacturing

The following additional security objectives for the operational environment are defined in this Security Target:

**Table 15. Additional security objectives for the operational environment defined in this Security Target**

Name	Title
OE.Secure-Values	Generation of secure values
OE.Terminal-Support	Terminal support to ensure integrity, confidentiality and use of random numbers

The TOE provides specific functionality that requires the TOE Manufacturer to implement measures for the unique identification of the TOE. Therefore, OE.Secure-Values is defined to allow a TOE specific implementation (refer also to A.Secure-Values).

**OE.Secure-Values**

**Generation of Secure Values**

The environment shall generate confidential and cryptographically strong keys for authentication purpose. These values are generated outside the TOE and are downloaded to the TOE during the personalisation or usage in phase 5 to 7.

The TOE provides specific functionality to verify the success of the application download process. Therefore, OE.Terminal-Support is defined to allow triggering the verification process.

**OE.Terminal-Support**

**Terminal support to ensure integrity, confidentiality and use of random numbers**

The terminal shall verify information sent by the TOE in order to ensure integrity and confidentiality of the communication. This involves checking of MAC values, verification of redundancy information according to the cryptographic protocol and secure closing of the communication session. Furthermore the terminal shall provide random numbers according to AIS20 or AIS31 for the authentication.

The additional security objectives for the operational environment as defined above are required for the correct functioning of the DESFire security functionality. As the Protection Profile [6] does not cover this kind of functionality, the additional objectives neither mitigate a threat (or a part of a threat) meant to be addressed by security objectives for the TOE in the Protection Profile [6], nor fulfil an OSP (or part of an OSP) meant to be addressed by security objectives for the TOE in the Protection Profile [6].

**4.4 Security Objectives Rationale**

Section 4.4 in the Protection Profile [6] provides a rationale how the threats, organisational security policies and assumptions are addressed by the security objectives defined in the Protection Profile. This rationale is not repeated here.



The following table summarizes how threats, organisational security policies and assumptions are addressed by the security objectives with respect to those items defined in the Security Target. All these items are in line with those in the Protection Profile [6].

**Table 16. Security Problem Definition mapping to Security Objective**

Security Problem Definition	Security Objective
T.Data-Modification	O.Access-Control O.Type-Consistency OE.Terminal-Support
T.Impersonate	O.Authentication
T.Cloning	O.Access-Control O.Authentication
P.Encryption	O.Encryption
P.MAC	O.MAC
P.Transaction	O.Transaction
P.No-Trace	O.Access-Control O.Authentication O.No-Trace
A.Secure-Values	OE.Secure-Values
A.Terminal-Support	OE.Terminal-Support

The rationale for the mapping is given below:

**Justification related to T.Data-Modification:**

Security Objective	Rationale
O.Access-Control	This objective requires an access control mechanism that limits the ability to modify data and code elements stored by the TOE.
O.Type-Consistency	This objective ensures that data types are adhered, so that TOE data can not be modified by abusing type-specific operations.
OE.Terminal-Support	This objective requires that the terminal must support this by checking the TOE responses.

**Justification related to T.Impersonate:**

Security Objective	Rationale
O.Authentication	This objective requires that the authentication mechanism provided by the TOE shall be resistant against attack scenarios targeting the impersonation of authorized users.

**Justification related to T.Cloning:**

Security Objective	Rationale
O.Access-Control	This objective requires that unauthorized users can not read any information that is restricted to the authorized subjects. The cryptographic keys used for the authentication are stored inside the TOE and are protected by this objective. This objective states that no keys used for authentication shall ever be output.

Security Objective	Rationale
O.Authentication	This objective requires that users are authenticated before they can read any information that is restricted to authorized users.

**Justification related to A.Secure-Values:**

Security Objective	Rationale
OE.Secure-Values	This objective is an immediate transformation of the assumption, therefore it covers the assumption.

**Justification related to A.Terminal-Support:**

Security Objective	Rationale
OE.Terminal-Support	This objective is an immediate transformation of the assumption, therefore it covers the assumption. The TOE can only check the integrity of data received from the terminal. For data transferred to the terminal the receiver must verify the integrity of the received data. Furthermore the TOE cannot verify the entropy of the random number sent by the terminal. The terminal itself must ensure that random numbers are generated with appropriate entropy for the authentication. This is assumed by the related assumption, therefore the assumption is covered.

**Justification related to P.Encryption:**

Security Objective	Rationale
O.Encryption	This objective is an immediate transformation of the security policy, therefore it covers the security policy.

**Justification related to P.MAC:**

Security Objective	Rationale
O.MAC	This objective is an immediate transformation of the security policy, therefore it covers the security policy.

**Justification related to P.Transaction:**

Security Objective	Rationale
O.Transaction	This objective is an immediate transformation of the security policy, therefore it covers the security policy.

**Justification related to P.No-Trace:**

Security Objective	Rationale
O.Access-Control	This objective provides means to implement access control to data elements on the TOE in order to prevent tracing based on freely accessible data elements.
O.Authentication	This objective provides means to implement authentication on the TOE in order to prevent tracing based on freely accessible data elements.

Security Objective	Rationale
O.No-Trace	This objective requires that the TOE shall provide an option to prevent the transfer of any information that is suitable for tracing an end-user by an unauthorized subject. This objective includes the UID.

The justification of the additional policies and the additional assumptions show that they do not contradict the rationale already given in the Protection Profile [\[6\]](#) for the assumptions, policy and threats defined there.

## 5 Extended Components Definition

---

This Security Target does not define extended components.

Note that the Protection Profile [\[6\]](#) defines extended security functional requirements FCS\_RNG.1, FMT\_LIM.1, FMT\_LIM.2, FAU\_SAS.1 and FDP\_SDC.1 in chapter 5, which are included in this Security Target.

## 6 Security Requirements

This chapter defines the security requirements that shall be met by the TOE. These security requirements are composed of the security functional requirements and the security assurance requirements that the TOE must meet in order to achieve its security objectives.

CC allows several operations to be performed on security requirements (on the component level); refinement, selection, assignment, and iteration are defined in section 8.1 of CC Part 1 [2]. These operations are used in the Protection Profile [6] and in this Security Target, respectively.

The refinement operation is used to add details to requirements, and thus, further intensifies a requirement.

The selection operation is used to select one or more options provided by the Protection Profile or CC in stating a requirement. Selections having been made are denoted as italic text.

The assignment operation is used to assign a specific value to an unspecified parameter, such as the length of a password. Assignments having been made are denoted as italic text.

The iteration operation is used when a component is repeated with varying operations. For the sake of a better readability, the iteration operation may also be applied to some single components (being not repeated) in order to indicate belonging of such SFRs to same functional cluster. In such a case, the iteration operation is applied to only one single component.

Whenever an element in the Protection Profile contains an operation that is left uncompleted, the Security Target has to complete that operation.

### 6.1 Security Functional Requirements

#### 6.1.1 Security Functional Requirements from the Protection Profile

##### 6.1.1.1 FAU\_SAS.1

The TOE shall meet the requirement "Audit storage" as defined in the PP [6], and as specified below.

<b>FAU_SAS.1</b>	<b>Audit storage</b>
Hierarchical to:	No other components.
Dependencies:	No dependencies.
FAU_SAS.1.1	The TSF shall provide <i>the test process before TOE Delivery</i> with the capability to store <i>the Initialisation Data, Pre-personalisation Data, Customer-specific Data</i> <sup>1</sup> in the <i>non-volatile memory</i> <sup>2</sup> .

<sup>1</sup> [selection: *the Initialisation Data, Pre-personalisation Data, [assignment: other data]*]

<sup>2</sup> [assignment: *type of persistent memory*]

6.1.1.2 FCS\_RNG.1/PTG2

The TOE shall meet the requirement "Random number generation (Class PTG.2)" as defined in the PP [6] according to [1], and as specified below.

**FCS\_RNG.1/PTG2 Random number generation (Class PTG.2)**

Hierarchical to: No other components.

Dependencies: No dependencies.

FCS\_RNG.1.1/PTG2 The TSF shall provide a *physical*<sup>3</sup> random number generator that implements:<sup>4</sup>

(PTG.2.1) A total failure test detects a total failure of entropy source immediately when the RNG has started. When a total failure is detected, no random numbers will be output.

(PTG.2.2) If a total failure of the entropy source occurs while the RNG is being operated, the RNG *prevents the output of any internal random number that depends on some raw random numbers that have been generated after the total failure of the entropy source*<sup>5</sup>.

(PTG.2.3) The online test shall detect non-tolerable statistical defects of the raw random number sequence (i) immediately when the RNG has started, and (ii) while the RNG is being operated. The TSF must not output any random numbers before the power-up online test has finished successfully or when a defect has been detected.

(PTG.2.4) The online test procedure shall be effective to detect non-tolerable weaknesses of the random numbers soon.

(PTG.2.5) The online test procedure checks the quality of the raw random number sequence. It is triggered *at regular intervals or continuously*<sup>6</sup>. The online test is suitable for detecting non-tolerable statistical defects of the statistical properties of the raw random numbers within an acceptable period of time.

FCS\_RNG.1.2/PTG2 The TSF shall provide *octets of bits*<sup>7</sup> that meet:

3 [selection: *physical, hybrid physical, hybrid deterministic*]

4 [assignment: *list of security capabilities*]

5 [selection: *prevents the output of any internal random number that depends on some raw random numbers that have been generated after the total failure of the entropy source, generates the internal random numbers with a post-processing algorithm of class DRG.2 as long as its internal state entropy guarantees the claimed output entropy*]

6 [selection: *externally, at regular intervals, continuously, applied upon specified internal events*]

7 [selection: *bits, octets of bits, numbers* [assignment: *format of the numbers*]]

(PTG.2.6) Test procedure A<sup>8</sup> does not distinguish the internal random numbers from output sequences of an ideal RNG.

(PTG.2.7) The average Shannon entropy per internal random bit exceeds 0.997.

**6.1.1.3 FCS\_RNG.1/PTG3**

The TOE shall meet the requirement "Random number generation (Class PTG.3)" as defined in the PP [6] according to [1], and as specified below.

**FCS\_RNG.1/PTG3 Random number generation (Class PTG.3)**

Hierarchical to: No other components.

Dependencies: No dependencies.

FCS\_RNG.1.1/PTG3 The TSF shall provide a *hybrid physical*<sup>9</sup> random number generator that implements:<sup>10</sup>

(PTG.3.1) A total failure test detects a total failure of entropy source immediately when the RNG has started. When a total failure has been detected no random numbers will be output.

(PTG.3.2) If a total failure of the entropy source occurs while the RNG is being operated, the RNG *prevents the output of any internal random number that depends on some raw random numbers that have been generated after the total failure of the entropy source*<sup>11</sup>.

(PTG.3.3) The online test shall detect non-tolerable statistical defects of the raw random number sequence (i) immediately when the RNG is started, and (ii) while the RNG is being operated. The TSF must not output any random numbers before the power-up online test and the seeding of the DRG.3 post-processing algorithm have been finished successfully or when a defect has been detected.

(PTG.3.4) The online test procedure shall be effective to detect non-tolerable weaknesses of the random numbers soon.

(PTG.3.5) The online test procedure checks the raw random number sequence. It is triggered *continuously*<sup>12</sup>. The online

8 [assignment: *additional standard test suites*]. Assignment is empty as per Application Note 44 of the PP.

9 [selection: *physical, hybrid physical, hybrid deterministic*]

10 [assignment: *list of security capabilities*]

11 [selection: *prevents the output of any internal random number that depends on some raw random numbers that have been generated after the total failure of the entropy source, generates the internal random numbers with a post-processing algorithm of class DRG.3 as long as its internal state entropy guarantees the claimed output entropy*]

12 [selection: *externally, at regular intervals, continuously, upon specified internal events*]

test is suitable for detecting non-tolerable statistical defects of the statistical properties of the raw random numbers within an acceptable period of time.

(PTG.3.6) The algorithmic post-processing algorithm belongs to Class DRG.3 with cryptographic state transition function and cryptographic output function, and the output data rate of the post-processing algorithm shall not exceed its input data rate.

FCS\_RNG.1.2/PTG3 The TSF shall provide *random numbers*<sup>13</sup> that meet:

(PTG.3.7) Statistical test suites cannot practically distinguish the internal random numbers from output sequences of an ideal RNG. The internal random numbers must pass test procedure A *and no additional test suites*<sup>14</sup>.

(PTG.3.8) The internal random numbers shall use PTRNG of class PTG.2 as random source for the post-processing<sup>15</sup>.

**6.1.1.4 FCS\_RNG.1/DRG4**

The TOE shall meet the requirement "Random number generation (Class DRG.4)" as defined in the PP [6] according to [1], and as specified below.

**FCS\_RNG.1/DRG4 Random number generation (Class DRG.4)**

Hierarchical to: No other components.

Dependencies: No dependencies.

FCS\_RNG.1.1/DRG4 The TSF shall provide a *hybrid deterministic*<sup>16</sup> random number generator that implements:<sup>17</sup>

(DRG.4.1)The internal state of the RNG shall use PTRNG of class PTG.2 as random source<sup>18</sup>.

(DRG.4.2) The RNG provides forward secrecy.

(DRG.4.3) The RNG provides backward secrecy even if the current internal state is known.

13 [selection: *bits, octets of bits, numbers* [assignment: *format of the numbers*]]

14 [assignment: *additional test suites*]

15 [selection: *use PTRNG of class PTG.2 as random source for the post-processing, have* [assignment: *work factor*], *require* [assignment: *guess work*]]

16 [selection: *physical, hybrid physical, hybrid deterministic*]

17 [assignment: *list of security capabilities*]

18 [selection: *use PTRNG of class PTG.2 as random source, have* [assignment: *work factor*], *require* [assignment: *guess work*]]



(DRG.4.4) The RNG provides enhanced forward secrecy *on demand*<sup>19</sup>.

(DRG.4.5) The internal state of the RNG is seeded by an *PTRNG of class PTG.2*<sup>20</sup>.

FCS\_RNG.1.2/  
DRG4

The TSF shall provide random numbers that meet:

(DRG.4.6) The RNG generates output for which *for AES-mode*  $2^{48}$  *and for TDEA-mode*  $2^{35}$  <sup>21</sup> strings of bit length 128 are mutually different with probability *at least*  $1 - 2^{-24}$ <sup>22</sup>.

(DRG.4.7) Statistical test suites cannot practically distinguish the random numbers from output sequences of an ideal RNG. The random numbers must pass test procedure A *and no additional test suites*<sup>23</sup>.

**6.1.1.5 FDP\_SDC.1**

The TOE shall meet the requirement "Stored data confidentiality" as defined in the PP [6], and as specified below.

**FDP\_SDC.1                      Stored data confidentiality**

Hierarchical to:              No other components.

Dependencies:                No dependencies.

FDP\_SDC.1.1                The TSF shall ensure the confidentiality of the information of the user data while it is stored in the *ROM, RAM and non-volatile memory*<sup>24</sup>.

**6.1.1.6 FDP\_SDI.2**

The TOE shall meet the requirement "Stored data integrity monitoring and action" as defined in the PP [6], and as specified below.

**FDP\_SDI.2                      Stored data integrity monitoring and action**

Hierarchical to:              FDP\_SDI.1 Stored data integrity monitoring

Dependencies:                No dependencies.

19 [selection: *on demand, on condition [assignment: condition], after [assignment: time]*  
 20 [selection: *internal entropy source, PTRNG of class PTG.2, PTRNG of class PTG.3, [other selection]*  
 21 [assignment: *number of strings*]  
 22 [assignment: *probability*]  
 23 [assignment: *additional test suites*]  
 24 [assignment: *memory area*]

- FDP\_SDI.2.1 The TSF shall monitor user data stored in containers controlled by the TSF for *modification, deletion, repetition or loss of data*<sup>25</sup> on all objects, based on the following attributes: *integrity check information associated with the data stored in memories*<sup>26</sup>.
- FDP\_SDI.2.2 Upon detection of a data integrity error, the TSF shall *perform an error correction if possible or trigger a Security Reset if not*<sup>27</sup>.

**6.1.2 Security Functional Requirements regarding Access Control**

**6.1.2.1 DESFire Access Control Policy**

The Security Function Policy (SFP) *DESFire Access Control Policy* uses the definitions listed in this paragraph. The defined subjects are:

Subject	Admin Administrator
Info	The Admin is the subject that owns or has access to the PICCMasterKey.
Info	The Admin is the subject that distributes the PICCDAMAuthKey, DAMMACs, and DAMENCs containing the AppDAMDefaultKey, to the DelAppMgr.

Subject	AppMgr Application Manager
Info	The AppMgr is the subject that owns or has access to an AppMasterKey. Note that the TOE supports multiple <i>Applications</i> and therefore multiple AppMgr, however for one Application there is only one AppMgr.

Subject	DelAppMgr Delegated Application Manager
Info	The DelAppMgr is the subject that has access to a valid DAMMAC, the PICCDAMAuthKey, and a DAMENC containing the AppDAMDefaultKey. Note that the TOE supports multiple DelApplications and therefore multiple DelAppMgr.

Subject	AppUser Application User
Info	The AppUser is the subject that owns or has access to an AppKey. Note that the TOE supports multiple AppUser within each Application and the assigned rights to the AppUser can be different, which allows to have more or less powerful AppUser.

25 [assignment: *integrity errors*]  
 26 [assignment: *user data attributes*]  
 27 [assignment: *action to be taken*]

Subject	AppChangeUser	Application Change User
Info	The AppChangeUser is the subject that owns or has access to an AppChangeKey.	

Subject	AppRollUser	Application Roll Key Set User
Info	The AppRollUser is the subject that owns or has access to an AppRollKey.	

Subject	OrigKeyUser	Originality Key User
Info	The OrigKeyUser is the subject that owns or has access to an OriginalityKey. The OrigKeyUser can authenticate with the TOE to prove the authenticity of the Security IC.	

Subject	Anybody	Anybody
Info	Any subject that does not belong to one of the roles Admin, AppMgr, DelAppMgr, AppUser, AppChangeUser, AppRollUser or OrigKeyUser, belongs to the role Anybody. This role includes the card holder (also referred to as end-user), and any other subject like an attacker for instance. The subjects belonging to Anybody do not possess any key and therefore are not able to perform any operation that is restricted to one of the roles which are explicitly excluded from the role Anybody.	

Subject	Nobody	Nobody
Info	Any subject that does not belong to one of the roles Admin, AppMgr, DelAppMgr, AppUser, AppChangeUser, AppRollUser, OrigKeyUser or Anybody, belongs to the role Nobody. Due to the definition of Anybody, the set of all subjects belonging to the role Nobody is the empty set.	

The objects defined for the *DESFire Access Control Policy* are:

Object	PICCLevelData	PICC Level Data
Info	The PICC level is the lowest level of the MIFARE DESFire Software (PICC level, Application level, File level). On the PICC level Application and DelApplication can be created or deleted. Hence to the PICCLevelData belong Application and DelApplication.	
Operation	Modify	Modify attributes of PICCLevelData.
Operation	Freeze	Freeze attributes of PICCLevelData.PICCKeySettings.
Attribute	PICCKeySettings	Generic PICC key settings.

Object	Application	Application
Info	The card can store a number of Application. An Application can store a number of File.	
Operation	Modify	Modify attribute Application.AppKeySettings.
Operation	Freeze	Freeze attribute Application.AppKeySettings.
Operation	Create	Create an Application.
Operation	Delete	Delete an Application.
Operation	Select	Select an Application.
Attribute	AppKeySettings	Generic application key settings.

Object	DelApplication	Delegated Application
Info	The card can store a number of DelApplication. After creation the DelApplication has the same attributes as a Application.	
Operation	Create	Create a DelApplication.
Operation	Delete	Delete a DelApplication.

Object	File	File
Info	An Application can store a number of File of different types.	
Operation	Create	Create a File.
Operation	Delete	Delete a File.
Operation	Freeze	Freeze attributes of File.
Operation	Read	Read operations accessing the content of a File.
Operation	Write	Write operations accessing the content of a File.
Operation	ReadWrite	ReadWrite operations accessing the content of a File.
Operation	Change	Change operation to change the attribute File.AccessRights
Attribute	AccessRights	Generic access rights for File.

Object	PICCMasterKey	PICC Master Key
Info	The Card Master Key.	
Operation	Change	Change the PICCMasterKey.
Operation	Freeze	Freeze the PICCMasterKey.

Object	PICCApDefaultKey	PICC Application Default Key
Info	The Default Application Master Key and Application Keys that are used when an application is created and when a KeySet is initialized.	
Operation	Change	Change the PICCApDefaultKey.

Object	PICCDAMAuthKey	PICC DAM Authentication Key
Info	Delegated Application Management Authentication Key.	
Operation	Change	Change the PICCDAMAuthKey.

Object	PICCDAMENCKey	PICC DAM Encryption Key
Info	Delegated Application Management Encryption Key to generate DAMENC.	
Operation	Change	Change the PICCDAMENCKey.

Object	PICCDAMMACKey	PICC DAM MAC Key
Info	Delegated Application Management MAC Key to generate DAMMAC.	
Operation	Change	Change the PICCDAMMACKey.

Object	OriginalityKey	Originality Key
Info	Key to check the originality of the card.	

Object	AppMasterKey	Application Master Key
Info	Application Master Key.	
Operation	Change	Change the AppMasterKey.
Operation	Freeze	Freeze the AppMasterKey.

Object	AppChangeKey	Application Change Key
Info	Application Change Key.	
Operation	Change	Change the AppChangeKey.

Object	AppKey	Application Key
Info	Application Key.	

Object	AppKey	Application Key
Operation	Change	Change the AppKey.

Object	AppTransactionMACKey	Application Transaction MAC Key
Info	Application Transaction MAC Key.	
Operation	Create	Create the AppTransactionMACKey.
Operation	Delete	Delete the AppTransactionMACKey.

Object	AppRollKey	Application Roll Key Set Key
Info	Application Roll Key Set Key.	
Operation	Change	Change the AppRollKey.

Object	AppDAMDefaultKey	Application DAM Default Key
Info	Delegated Application Management Default Authentication Key	

Object	KeySet	Key Set
Info	AppKeys are grouped into KeySets.	
Operation	Roll	Roll the KeySet.

Note that subjects are authorized by cryptographic keys. These keys are considered as authentication data and not as security attributes of the subjects. The card has a card master key PICCMasterKey. Every Application has an AppMasterKey and a variable number of AppKeys organized in KeySet used for operations on Files (all these keys are called Application Keys). The Application Keys and Key Sets within an application are numbered.

### 6.1.2.2 FDP\_ACC.1/DF

The TOE shall meet the requirement "Subset access control" as specified below.

**FDP\_ACC.1/DF**      **Subset access control**

Hierarchical to:      No other components.

Dependencies:      FDP\_ACF.1 Security attribute based access control

FDP\_ACC.1.1/DF The TSF shall enforce the *DESFire Access Control Policy*<sup>28</sup> on all subjects, objects, operations and attributes defined by the *DESFire Access Control Policy*<sup>29</sup>.

**6.1.2.3 FDP\_ACF.1/DF**

The TOE shall meet the requirement "Security attribute based access control" as specified below.

**FDP\_ACF.1/DF Security attribute based access control**

Hierarchical to: No other components.

Dependencies: FDP\_ACC.1 Subset access control, FMT\_MSA.3 Static attribute initialisation

FDP\_ACF.1.1/DF The TSF shall enforce the *DESFire Access Control Policy*<sup>30</sup> to objects based on the following: all subjects, objects and attributes<sup>31</sup>.

FDP\_ACF.1.2/DF The TSF shall enforce the following rules to determine if an operation among controlled subjects and controlled objects is allowed:<sup>32</sup>

1. *The Admin is allowed to perform Application.Create and Application.Delete.*
2. *The Admin is allowed to perform DelApplication.Delete.*
3. *The AppMgr is allowed to perform File.Create and File.Delete.*
4. *The DelAppMgr is allowed to perform DelApplication.Create with valid DAMMAC and valid DAMENC.*

FDP\_ACF.1.3/DF The TSF shall explicitly authorise access of subjects to objects based on the following additional rules:<sup>33</sup>

1. *The AppMgr is allowed to Application.Delete if the attribute PICCLLevelData.PICCKeySettings grant this right.*
2. *The AppUser is allowed to perform File.Read or File.Write or File.ReadWrite or File.Change on File if the File.AccessRights grant these rights.*
3. *The Anybody is allowed to perform Application.Create if the PICCLLevelData.PICCKeySettings grant this right.*
4. *The Anybody is allowed to perform File.Create and File.Delete if the Application.AppKeySettings grant these rights.*

28 [assignment: access control SFP]

29 [assignment: list of subjects, objects, and operations among subjects and objects covered by the SFP]

30 [assignment: access control SFP]

31 [assignment: list of subjects and objects controlled under the indicated SFP, and for each, the SFP-relevant security attributes, or named groups of SFP-relevant security attributes]

32 [assignment: rules governing access among controlled subjects and controlled objects using controlled operations on controlled objects]

33 [assignment: rules, based on security attributes, that explicitly authorise access of subjects to objects]

5. *The Anybody is allowed to perform File.Read or File.Write or File.ReadWrite or File.Change if the File.AccessRights grant these rights.*

FDP\_ACF.1.4/DF The TSF shall explicitly deny access of subjects to objects based on the following additional rules:<sup>34</sup>

1. *No one but Nobody is allowed to perform File.Read or File.Write or File.ReadWrite or File.Change if theFile.AccessRights do not grant this right.*
2. *OrigKeyUser is not allowed to perform any operation on objects.*
3. *No one but Nobody is allowed to perform any operation on OriginalityKey.*

**6.1.2.4 FDP\_ITC.2/DF**

The TOE shall meet the requirement "Import of user data with security attributes" as specified below.

**FDP\_ITC.2/DF Import of user data with security attributes**

Hierarchical to: No other components.

Dependencies: [FDP\_ACC.1 Subset access control, or FDP\_IFC.1 Subset information flow control], [FTP\_ITC.1 Inter-TSF trusted channel, or FTP\_TRP.1 Trusted path], FPT\_TDC.1 Inter-TSF basic TSF data consistency

FDP\_ITC.2.1/DF The TSF shall enforce the *DESFire Access Control Policy*<sup>35</sup> when importing user data, controlled under the SFP, from outside of the TOE.

FDP\_ITC.2.2/DF The TSF shall use the security attributes associated with the imported user data.

FDP\_ITC.2.3/DF The TSF shall ensure that the protocol used provides for the unambiguous association between the security attributes and the user data received.

FDP\_ITC.2.4/DF The TSF shall ensure that interpretation of the security attributes of the imported user data is as intended by the source of the user data.

FDP\_ITC.2.5/DF The TSF shall enforce the following rules when importing user data controlled under the SFP from outside the TOE: *no additional rules*<sup>36</sup>.

<sup>34</sup> [assignment: *rules, based on security attributes, that explicitly deny access of subjects to objects*]

<sup>35</sup> [assignment: *access control SFP(s) and/or information flow control SFP(s)*]

<sup>36</sup> [assignment: *additional importation control rules*]



### 6.1.2.5 FMT\_MSA.1/DF

The TOE shall meet the requirement "Management of security attributes" as specified below.

#### **FMT\_MSA.1/DF      Management of security attributes**

Hierarchical to:      No other components.

Dependencies:      [FDP\_ACC.1 Subset access control, or FDP\_IFC.1 Subset information flow control], FMT\_SMR.1 Security roles, FMT\_SMF.1 Specification of Management Functions

FMT\_MSA.1.1/DF      The TSF shall enforce the *DESFire Access Control Policy*<sup>37</sup> to restrict the ability to *modify or freeze and change*<sup>38</sup> the security attributes of the objects *PICCLevelData*, *Application* and the security attribute *File.AccessRights*<sup>39</sup> to the *Admin*, *AppMgr* and *AppChangeUser* respectively<sup>40</sup>.

**Refinement:**      The detailed management abilities are:

1. *Only the Admin is allowed to perform PICCLevelData.Modify or PICCLevelData.Freeze on PICCLevelData.PICCKeySettings.*
2. *Only the AppMgr is allowed to perform Application.Modify or Application.Freeze on Application.AppKeySettings.*
3. *The AppChangeUser is allowed to perform File.Freeze on File.AccessRights.*

### 6.1.2.6 FMT\_MSA.3/DF

The TOE shall meet the requirement "Static attribute initialization" as specified below.

#### **FMT\_MSA.3/DF      Static attribute initialization**

Hierarchical to:      No other components.

Dependencies:      FMT\_MSA.1 Management of security attributes, FMT\_SMR.1 Security roles

FMT\_MSA.3.1/DF      The TSF shall enforce the *DESFire Access Control Policy*<sup>41</sup> to provide *permissive*<sup>42</sup> default values for security attributes that are used to enforce the SFP.

<sup>37</sup> [assignment: *access control SFP(s)*, *information flow control SFP(s)*]

<sup>38</sup> [selection: *change\_default*, *query*, *modify*, *delete*, [assignment: *other operations*]]

<sup>39</sup> [assignment: *list of security attributes*]

<sup>40</sup> [assignment: *the authorised identified roles*]

<sup>41</sup> [assignment: *access control SFP*, *information flow control SFP*]

<sup>42</sup> [selection, choose one of: *restrictive*, *permissive*, [assignment: *other property*]]

FMT\_MSA.3.2/DF The TSF shall allow the *no one but Nobody*<sup>43</sup> to specify alternative initial values to override the default values when an object or information is created.

**Application Note:** The only initial attributes are the card attributes. All other attributes have to be defined at the same time the respective object is created.

**6.1.2.7 FMT\_MTD.1/DF**

The TOE shall meet the requirement "Management of TSF data" as specified below.

**FMT\_MTD.1/DF Management of TSF data**

Hierarchical to: No other components.

Dependencies: FMT\_SMR.1 Security roles, FMT\_SMF.1 Specification of Management Functions

FMT\_MTD.1.1/DF The TSF shall restrict the ability to *perform*<sup>44</sup> the operations *PICCMasterKey.Change*, *PICCMasterKey.Freeze*, *PICCAAppDefaultKey.Change*, *AppMasterKey.Change*, *AppMasterKey.Freeze*, *AppChangeKey.Change*<sup>45</sup> to the *Admin*, *AppMgr* and *AppUser*<sup>46</sup>.

**Refinement:** The detailed management abilities are:

1. *Only the Admin is allowed to perform PICCMasterKey.Change or PICCMasterKey.Freeze.*
2. *The Admin is allowed to perform PICCAAppDefaultKey.Change.*
3. *The Admin is allowed to perform PICCDAMAAuthKey.Change.*
4. *The Admin is allowed to perform PICCDAMENCKKey.Change.*
5. *The Admin is allowed to perform PICCDAMMACKKey.Change.*
6. *The AppMgr is allowed to perform AppMasterKey.Change and AppMasterKey.Freeze.*
7. *The AppMgr is allowed to perform AppChangeKey.Change.*
8. *The AppMgr is allowed to perform AppKey.Change.*
9. *The AppMgr is allowed to perform AppRollKey.Change.*
10. *The AppMgr is allowed to perform AppTransactionMACKey.Create and AppTransactionMACKey.Delete.*
11. *The AppChangeUser is allowed to perform AppChangeKey.Change.*
12. *The AppChangeUser is allowed to perform AppKey.Change.*
13. *The AppUser is allowed to perform AppKey.Change on AppKey if Application.AppKeySettings grant this right.*

43 [assignment: *the authorised identified roles*]

44 [selection: *change\_default, query, modify, delete, clear, [assignment: other operations]*]

45 [assignment: *list of TSF data*]

46 [assignment: *the authorised identified roles*]

- 14. The AppUser is allowed to perform AppTransactionMACKey.Create and AppTransactionMACKey.Delete on AppTransactionMACKey if Application.AppKeySettings grant this right.
- 15. The AppRollUser is allowed to perform KeySet.Roll.

**6.1.2.8 FMT\_SMF.1/DF**

The TOE shall meet the requirement "Specification of Management Functions" as specified below.

**FMT\_SMF.1/DF Specification of Management Functions**

Hierarchical to: No other components.

Dependencies: No dependencies.

FMT\_SMF.1.1/DF The TSF shall be capable of performing the following management functions:<sup>47</sup>

- Authenticate a user
- Invalidating the current authentication state based on the functions: Selecting an application or the card, Changing the key corresponding to the current authentication, Occurrence of any error during the execution of a command, starting a new authentication, Rolling key set, Failed Proximity Check, Deleting an Application as AppMgr; Reset;
- Changing a security attribute
- Rolling the Key Set
- Creating or deleting an application, a delegated application or a file
- Selection of the Virtual Card

**6.1.2.9 FMT\_SMR.1/DF**

The TOE shall meet the requirement "Security roles" as specified below.

**FMT\_SMR.1/DF Security roles**

Hierarchical to: No other components.

Dependencies: FIA\_UID.1 Timing of identification

FMT\_SMR.1.1/DF The TSF shall maintain the roles Admin, AppMgr, DelAppMgr, AppUser, AppChangeUser, AppRollUser, OrigKeyUser and Anybody<sup>48</sup>.

FMT\_SMR.1.2/DF The TSF shall be able to associate users with roles.

<sup>47</sup> [assignment: list of management functions to be provided by the TSF]

<sup>48</sup> [assignment: the authorised identified roles]

6.1.2.10 Implications of the DESFire Access Control Policy

The DESFire Access Control Policy has some implications, that can be drawn from the policy and that are essential parts of the TOE security functions:

- The TOE end-user does normally not belong to the group of authorised users (Admin, AppMgr, DelAppMgr, AppUser), but regarded as Anybody by the TOE. This means that the TOE cannot determine if it is used by its intended end-user (in other words: it cannot determine if the current card holder is the owner of the card).
- The Admin can have the exclusive right to create and delete Applications on the card, however he can also grant this privilege to Anybody. In the case of DelApplications the Admin can grant this privilege to the AppMgr. Additionally, changing the PICCLevelData is reserved for the Admin. AppKeys, at delivery time should be personalized to a preliminary, temporary key only known to the Admin and the AppMgr.
- At Application personalization time, the AppMgr uses the preliminary AppKey in order to personalize the AppKeys, whereas all keys, except the AppMasterKey, can be personalized to a preliminary, temporary key only known to the AppMgr and the AppUser. Furthermore, the AppMgr has the right to create Files within his Application scope.

6.1.3 Security Functional Requirements regarding Confidentiality, Authentication and Integrity

6.1.3.1 FCS\_COP.1/DF-DES

The TOE shall meet the requirement "Cryptographic Operation (DES)" as specified below.

**FCS\_COP.1/DF-DES      Cryptographic Operation (DES)**

Hierarchical to:      No other components.

Dependencies:      [FDP\_ITC.1 Import of user data without security attributes, or FDP\_ITC.2 Import of user data with security attributes, or FCS\_CKM.1 Cryptographic key generation], FCS\_CKM.4 Cryptographic key destruction

FCS\_COP.1.1/DF-DES      The TSF shall perform *encryption and decryption used for authentication*<sup>49</sup> in accordance with the specified cryptographic algorithm *Triple-DES in one of the following modes of operation: CBC and 3-key Triple-DES*<sup>50</sup> and cryptographic key sizes *168 bit*<sup>51</sup> that meet the following:<sup>52</sup>

- NIST SP 800-67 [13] (TDES)
- NIST SP 800-38A [11] (CBC mode)

49 [assignment: list of cryptographic operations]

50 [assignment: cryptographic algorithm]

51 [assignment: cryptographic key sizes]

52 [assignment: list of standards]

6.1.3.2 FCS\_COP.1/DF-AES

The TOE shall meet the requirement "Cryptographic Operation (AES)" as specified below.

**FCS\_COP.1/DF-AES Cryptographic Operation (AES)**

Hierarchical to: No other components.

Dependencies: [FDP\_ITC.1 Import of user data without security attributes, or FDP\_ITC.2 Import of user data with security attributes, or FCS\_CKM.1 Cryptographic key generation], FCS\_CKM.4 Cryptographic key destruction

FCS\_COP.1.1/DF-AES The TSF shall perform *encryption and decryption and cipher based MAC for authentication and communication*<sup>53</sup> in accordance with the specified cryptographic algorithm *Advanced Encryption Standard AES in one of the following modes of operation: CBC, CMAC*<sup>54</sup> and cryptographic key sizes *128 bits*<sup>55</sup> that meet the following.<sup>56</sup>

- FIPS PUB 197 [10] (AES)
- NIST SP 800-38A [11] (CBC mode)
- NIST SP 800-38B [12] (CMAC mode)

**Refinement:** For the MIFARE DESFire EV1 secure messaging the TOE uses the cryptographic algorithm for CMAC according to NIST Special Publication 800-38B [12] (CMAC mode) with the following modification: The TOE does not use the standard zero byte IV instead it uses an IV defined by the previous cryptographic operation (chaining mode).

6.1.3.3 FCS\_CKM.4/DF

The TOE shall meet the requirement "Cryptographic key destruction" as specified below.

**FCS\_CKM.4/DF Cryptographic key destruction**

Hierarchical to: No other components.

Dependencies: [FDP\_ITC.1 Import of user data without security attributes, or FDP\_ITC.2 Import of user data with security attributes, or FCS\_CKM.1 Cryptographic key generation]

53 [assignment: *list of cryptographic operations*]

54 [assignment: *cryptographic algorithm*]

55 [assignment: *cryptographic key sizes*]

56 [assignment: *list of standards*]

FCS\_CKM.4.1/DF The TSF shall destroy cryptographic keys in accordance with a specified cryptographic key destruction method *overwriting*<sup>57</sup> that meets the following: *none*<sup>58</sup>.

**6.1.3.4 FIA\_UAU.2/DF**

The TOE shall meet the requirement "User authentication before any action" as specified below.

**FIA\_UAU.2/DF                      User authentication before any action**

Hierarchical to:                      FIA\_UAU.1 Timing of authentication

Dependencies:                         FIA\_UID.1 Timing of identification

FIA\_UAU.2.1/DF                      The TSF shall require each user to be successfully authenticated before allowing any other TSF-mediated actions on behalf of that user.

**6.1.3.5 FIA\_UAU.5/DF**

The TOE shall meet the requirement "Multiple authentication mechanisms" as specified below.

**FIA\_UAU.5/DF                      Multiple authentication mechanisms**

Hierarchical to:                      No other components.

Dependencies:                         No dependencies.

FIA\_UAU.5.1/DF                      The TSF shall provide '*none*' and *cryptographic authentication*<sup>59</sup> to support user authentication.

FIA\_UAU.5.2/DF                      The TSF shall authenticate any user's claimed identity according to the *following rules*:<sup>60</sup>

- *The 'none' authentication is performed with anyone who communicates with the TOE without issuing an explicit authentication request. The 'none' authentication implicitly and solely authorizes the 'Everybody' subject.*
- *The cryptographic authentication is used to authorise the Administrator, Application Manager, Delegated Application Manager and Application User.*

57 [assignment: *cryptographic key destruction method*]

58 [assignment: *list of standards*]

59 [assignment: *list of multiple authentication mechanisms*]

60 [assignment: *rules describing how the multiple authentication mechanisms provide authentication*]

**6.1.3.6 FIA\_UID.2/DF**

The TOE shall meet the requirement "User identification before any action" as specified below.

**FIA\_UID.2/DF**                      **User identification before any action**

Hierarchical to:                      FIA\_UID.1 Timing of identification

Dependencies:                        No dependencies.

FIA\_UID.2.1/DF                      The TSF shall require each user to be successfully identified before allowing any other TSF-mediated actions on behalf of that user.

Application Note:                      Identification of a user is performed upon an authentication request based on the currently selected context and the key number. For example, if an authentication request for key number 0 is issued after selecting a specific application, the user is identified as the Application Manager of the respective application. Before any authentication request is issued the user is identified as "Everybody".

**6.1.3.7 FPT\_TDC.1/DF**

The TOE shall meet the requirement "Inter-TSF basic TSF data consistency" as specified below.

**FPT\_TDC.1/DF**                      **Inter-TSF basic TSF data consistency**

Hierarchical to:                        No other components.

Dependencies:                        No dependencies.

FPT\_TDC.1.1/DF                      The TSF shall provide the capability to consistently interpret *data files and values*<sup>61</sup> when shared between the TSF and another trusted IT product.

FPT\_TDC.1.2/DF                      The TSF shall use *the rule: data files or values can only be modified by their dedicated type-specific operations honouring the type-specific boundaries*<sup>62</sup> when interpreting the TSF data from another trusted IT product.

**6.1.3.8 FTP\_TRP.1/DF**

The TOE shall meet the requirement "Trusted path" as specified below.

**FTP\_TRP.1/DF**                      **Trusted path**

<sup>61</sup> [assignment: *list of TSF data types*]

<sup>62</sup> [assignment: *list of interpretation rules to be applied by the TSF*]

Hierarchical to:	No other components.
Dependencies:	No dependencies.
FTP_TRP.1.1/DF	The TSF shall provide a communication path between itself and <i>remote</i> <sup>63</sup> users that is logically distinct from other communication paths and provides assured identification of its end points and protection of the communicated data from <i>modification, disclosure, or only modification</i> <sup>64</sup> .
FTP_TRP.1.2/DF	The TSF shall permit <i>remote users</i> <sup>65</sup> to initiate communication via the trusted path.
FTP_TRP.1.3/DF	The TSF shall require the use of the trusted path for <i>authentication requests with 3 key Triple-DES or AES, confidentiality and/or integrity verification for data transfers protected with AES based on a setting in the file attributes</i> <sup>66</sup> .

## 6.1.4 Security Functional Requirements regarding Robustness

### 6.1.4.1 FDP\_ROL.1/DF

The TOE shall meet the requirement "Basic rollback" as specified below.

<b>FDP_ROL.1/DF</b>	<b>Basic rollback</b>
Hierarchical to:	No other components.
Dependencies:	[FDP_ACC.1 Subset access control, or FDP_IFC.1 Subset information flow control]
FDP_ROL.1.1/DF	The TSF shall enforce <i>DESFire Access Control Policy</i> <sup>67</sup> to permit the rollback of the <i>operations that modify the value or data file objects</i> <sup>68</sup> on the <i>backup files</i> <sup>69</sup> .
FDP_ROL.1.2/DF	The TSF shall permit operations to be rolled back within the <i>scope of the current transaction, which is defined by the following limitative events: chip reset, select command, deselect command, explicit commit, explicit abort, command failure</i> <sup>70</sup> .

63 [selection: *remote, local*]

64 [selection: *modification, disclosure, [assignment: other types of integrity or confidentiality violation]*]

65 [selection: *the TSF, local users, remote users*]

66 [selection: *initial user authentication, [assignment: other services for which trusted path is required]*]

67 [assignment: *access control SFP(s) and/or information flow control SFP(s)*]

68 [assignment: *list of operations*]

69 [assignment: *information and/or list of objects*]

70 [assignment: *boundary limit to which rollback may be performed*]



6.1.4.2 FPR\_UNL.1/DF

The TOE shall meet the requirement "Unlinkability" as specified below.

**FPR\_UNL.1/DF Unlinkability**

Hierarchical to: No other components.

Dependencies: No dependencies.

FPR\_UNL.1.1/DF The TSF shall ensure that *unauthorised subjects other than the card holder<sup>71</sup>* are unable to determine whether *any operation of the TOE<sup>72</sup> were caused by the same user<sup>73</sup>*.

6.1.4.3 FPT\_RPL.1/DF

The TOE shall meet the requirement "Replay detection" as specified below.

**FPT\_RPL.1/DF Replay detection**

Hierarchical to: No other components.

Dependencies: No dependencies.

FPT\_RPL.1.1/DF The TSF shall detect replay for the following entities: *authentication requests with 3-key Triple-DES or AES, confidentiality and/or data integrity verification for data transfers protected with AES and based on a setting in the file attributes<sup>74</sup>*.

FPT\_RPL.1.2/DF The TSF shall perform *rejection of the request<sup>75</sup>* when replay is detected.

6.2 Security Assurance Requirements

The following table lists all security assurance components that are valid for this Security Target.

Table 17. Security Assurance Requirements

Name	Title
ADV_ARC.1	Security architecture description
ADV_FSP.5	Complete semi-formal functional specification with additional error information
ADV_IMP.1	Implementation representation of the TSF
ADV_INT.2	Well-structured internals
ADV_TDS.4	Semiformal modular design

71 [assignment: *set of users and/or subjects*]

72 [assignment: *list of operations*]

73 [selection: *were caused by the same user, are related as follows[assignment: list of relations]*]

74 [assignment: *list of identified entities*]

75 [assignment: *list of specific actions*]

Name	Title
AGD_OPE.1	Operational user guidance
AGD_PRE.1	Preparative procedures
ALC_CMC.4	Production support, acceptance procedures and automation
ALC_CMS.5	Development tools CM coverage
ALC_DEL.1	Delivery procedures
ALC_DVS.2	Sufficiency of security measures
ALC_LCD.1	Developer defined life-cycle model
ALC_TAT.2	Compliance with implementation standards
ASE_INT.1	ST introduction
ASE_CCL.1	Conformance claims
ASE_SPD.1	Security problem definition
ASE_OBJ.2	Security objectives
ASE_ECD.1	Extended components definition
ASE_REQ.2	Derived security requirements
ASE_TSS.1	TOE summary specification (TSS)
ATE_COV.2	Analysis of coverage
ATE_DPT.3	Testing: modular design
ATE_FUN.1	Functional testing
ATE_IND.2	Independent testing - sample
AVA_VAN.5	Advanced methodical vulnerability analysis

## 6.2.1 Refinements of the TOE Security Assurance Requirements

In compliance to Application Note 23 in the PP, this Security Target has to conform to all refinements of the security assurance requirements in the PP. Because the refinements in the PP are defined for the security assurance components of EAL4 (augmented by ALC\_DVS.2 and AVA\_VAN.5), some refinements have to be applied to assurance components of the higher level EAL5 stated in the Security Target.

Most of the security assurance components mentioned in the PP and in this Security Target have the same component level and therefore for these components the refinements from the PP are valid for this Security Target without change. The following two subsections apply the refinements to ALC\_CMS.5 and ADV\_FSP.5, which are different between the PP and this Security Target.

### 6.2.1.1 Refinements Regarding ALC\_CMS

This Security Target requires a higher evaluation level for the CC family ALC\_CMS, namely ALC\_CMS.5 instead of ALC\_CMS.4. The refinement of the Protection Profile regarding ALC\_CMS.4 is a clarification of the configuration item "TOE implementation representation". Since in ALC\_CMS.5, the content and presentation of evidence element ALC\_CMS.5.1C only adds a further configuration item to the list of items to be tracked by the CM system, the refinement can be applied without changes.

The refinement of the original component ALC\_CMS.4 can be found in section 6.2.1.3 of the Protection Profile and is not repeated here.

**6.2.1.2 Refinements regarding ADV\_FSP**

This Security Target requires a higher evaluation level for the CC family ADV\_FSP, namely ADV\_FSP.5 instead of ADV\_FSP.4. The refinement of the Protection Profile regarding ADV\_FSP.4 is concerned with the complete representation of the TSF, the purpose and method of use of all TSFI, and the accuracy and completeness of the SFR instantiations. The refinement is not a change in the wording of the action elements, but a more detailed definition of the above items.

The higher level ADV\_FSP.5 requires a Functional Specification in a "semi-formal style" (ADV\_FSP.5.2C). The component ADV\_FSP.5 enlarges the scope of the error messages to be described from those resulting from an invocation of a TSFI (ADV\_FSP.5.6C) to also those not resulting from an invocation of a TSFI (ADV\_FSP.5.7C). For the latter a rationale shall be provided (ADV\_FSP.5.8C). Since the higher level ADV\_FSP.5 only affects the style of description and the scope of and rationale for error messages, the refinements can be applied without changes and are valid for ADV\_FSP.5.

The refinement of the original component ADV\_FSP.4 can be found in section 6.2.1.6 of the Protection Profile and is not cited here.

**6.3 Security Requirements Rationale**

**6.3.1 Rationale for the Security Functional Requirements**

Section 6.3.1 in the Protection Profile provides a rationale for the mapping between security functional requirements and security objectives defined in the Protection Profile. This rationale is not repeated here.

This Security Target defines additional SFRs for the TOE. In addition security requirements for the environment are defined. The following table gives an overview, how the requirements are combined to meet the security objectives.

**Table 18. Security Functional Requirements mapping to Security Objectives**

Name	Title
O.Access-Control	FCS_CKM.4/DF FDP_ACC.1/DF FDP_ACF.1/DF FDP_ITC.2/DF FMT_MSA.1/DF FMT_MSA.3/DF FMT_MTD.1/DF FMT_SMF.1/DF FMT_SMR.1/DF

Name	Title
O.Authentication	FCS_COP.1/DF-DES FCS_COP.1/DF-AES FIA_UID.2/DF FIA_UAU.2/DF FIA_UAU.5/DF FMT_SMF.1/DF FPT_RPL.1/DF FTP_TRP.1/DF
O.Encryption	FCS_CKM.4/DF FCS_COP.1/DF-AES FTP_TRP.1/DF
O.MAC	FCS_CKM.4/DF FCS_COP.1/DF-AES FPT_RPL.1/DF FTP_TRP.1/DF
O.Type-Consistency	FPT_TDC.1/DF
O.Transaction	FDP_ROL.1/DF
O.No-Trace	FPR_UNL.1/DF

**Justification related to Access Control (O.Access-Control)**

The SFR FMT\_SMR.1/DF defines the roles of the Access Control Policy. The SFR FDP\_ACC.1/DF and FDP\_ACF.1/DF define the rules and FMT\_MSA.3/DF and FMT\_MSA.1/DF the attributes that the access control is based on. FMT\_MTD.1/DF provides the rules for the management of the authentication data. The management functions are defined by FMT\_SMF.1/DF. Since the TOE stores data on behalf of the authorised subjects import of user data with security attributes is defined by FDP\_ITC.2/DF. Since cryptographic keys are used for authentication (refer to O.Authentication), these keys have to be removed if they are no longer needed for the access control (i.e. an application is deleted). This is required by FCS\_CKM.4/DF. These nine SFR together provide an access control mechanism as required by the objective O.Access-Control.

**Justification related to Authentication (O.Authentication)**

The two SFR FCS\_COP.1/DF-DES and FCS\_COP.1/DF-AES require that the TOE provides the basic cryptographic algorithms that can be used to perform the authentication. The SFR FIA\_UID.2/DF, FIA\_UAU.2/DF and FIA\_UAU.5/DF together define that users must be identified and authenticated before any action. The "none" authentication of FIA\_UAU.5/DF also ensures that a specific subject is identified and authenticated before an explicit authentication request is sent to the TOE. FMT\_SMF.1/DF defines security management functions the TSF shall be capable to perform. FTP\_TRP.1/DF requires a trusted communication path between the TOE and re- mote users, FTP\_TRP.1.3/DF especially requires "authentication requests". Together with FPT\_RPL.1/DF which requires a replay detection for these authentication requests the eight SFR fulfill the objective O.Authentication.

**Justification related to Confidential Communication (O.Encryption)**

The SFR FCS\_COP.1/DF-AES requires that the TOE provides the basic cryptographic algorithm AES that can be used to protect the communication by encryption. FTP\_TRP.1/DF requires a trusted communication path between the TOE and remote users,

FTP\_TRP.1.3/DF especially requires "confidentiality and/or data integrity verification for data transfers protected with AES and based on a setting in the file attributes". FCS\_CKM.4/DF requires that cryptographic keys used for encryption have to be removed after usage. These three SFR fulfill the objective O.Encryption.

**Justification related to Integrity-protected Communication (O.MAC)**

The SFR FCS\_COP.1/DF-AES requires that the TOE provides the basic cryptographic algorithms that can be used to compute a MAC which can protect the integrity of the communication. FTP\_TRP.1/DF requires a trusted communication path between the TOE and remote users, FTP\_TRP.1.3/DF especially requires "confidentiality and/or data integrity verification for data transfers on request of the file owner". FCS\_CKM.4/DF requires that cryptographic keys used for MAC operations have to be removed after usage. Together with FPT\_RPL.1/DF which requires a replay detection for these data transfers the four SFR fulfill the objective O.MAC.

**Justification related to Data type consistency (O.Type-Consistency)**

The SFR FPT\_TDC.1/DF requires the TOE to consistently interpret data files and values. The TOE will honor the respective file formats and boundaries (i.e. upper and lower limits, size limitations). This meets the objective O.Type-Consistency.

**Justification related to Transaction mechanism (O.Transaction)**

The SFR FDP\_ROL.1/DF requires the possibility to rollback a set of modifying operations on backup files in total. The set of operations is defined by the scope of the transaction, which is itself limited by some boundary events. This fulfils the objective O.Transaction.

**Justification related to Preventing Traceability (O.No-Trace)**

The SFR FPR\_UNL.1/DF requires that unauthorised subjects other than the card holder are unable to determine whether any operation of the TOE were caused by the same user. This meets the objective O.No-Trace.

**6.3.2 Dependencies of Security Functional Requirements**

The dependencies listed in the Protection Profile are independent of the additional dependencies listed in the table below. The dependencies of the Protection Profile are fulfilled within the Protection Profile and at least one dependency is considered to be satisfied. The following discussion demonstrates how the SFR dependencies (defined by Part 2 of the Common Criteria [3]) satisfy the requirements specified in [Section 6.1](#).

The dependencies and their fulfilment are listed in the tables below:

**Table 19. Dependencies of Security Functional Requirements (PP-0084)**

SFR	Dependency	Fulfilled in ST
FAU_SAS.1	No dependencies.	No dependency
FCS_RNG.1/PTG2	No dependencies.	No dependency
FCS_RNG.1/PTG3	No dependencies.	No dependency
FCS_RNG.1/DRG4	No dependencies.	No dependency
FDP_ITT.1	[FDP_ACC.1 Subset access control, or FDP_IFC.1 Subset information flow control]	Yes
FDP_IFC.1	FDP_IFF.1 Simple security attributes	See discussion in the PP
FDP_SDC.1	No dependencies.	No dependency

SFR	Dependency	Fullfilled in ST
FDP_SDI.2	No dependencies.	No dependency
FMT_LIM.1	FMT_LIM.2 Limited availability.	Yes
FMT_LIM.2	FMT_LIM.1 Limited capabilities.	Yes
FPT_FLS.1	No dependencies.	No dependency
FPT_ITT.1	No dependencies.	No dependency
FPT_PHP.3	No dependencies.	No dependency
FRU_FLT.2	FPT_FLS.1 Failure with preservation of secure state.	Yes

**Table 20. Dependencies of Security Functional Requirements (Security Target)**

SFR	Dependency	Fullfilled in ST
FCS_CKM.4/DF	[FDP_ITC.1 Import of user data without security attributes, or FDP_ITC.2 Import of user data with security attributes, or FCS_CKM.1 Cryptographic key generation]	Yes, by FDP_ITC.2/DF.
FCS_COP.1/DF-DES	[FDP_ITC.1 Import of user data without security attributes, or FDP_ITC.2 Import of user data with security attributes, or FCS_CKM.1 Cryptographic key generation], FCS_CKM.4 Cryptographic key destruction	Yes, by FDP_ITC.2/DF, FCS_CKM.4/DF.
FCS_COP.1/DF-AES	[FDP_ITC.1 Import of user data without security attributes, or FDP_ITC.2 Import of user data with security attributes, or FCS_CKM.1 Cryptographic key generation], FCS_CKM.4 Cryptographic key destruction	Yes, by FDP_ITC.2/DF, FCS_CKM.4/DF.
FDP_ACC.1/DF	FDP_ACF.1 Security attribute based access control	Yes, by FDP_ACF.1/DF.
FDP_ACF.1/DF	FDP_ACC.1 Subset access control, FMT_MSA.3 Static attribute initialisation	Yes, by FDP_ACC.1/DF.
FDP_ITC.2/DF	[FDP_ACC.1 Subset access control, or FDP_IFC.1 Subset information flow control], [FTP_ITC.1 Inter-TSF trusted channel, or FTP_TRP.1 Trusted path], FPT_TDC.1 Inter-TSF basic TSF data consistency	Yes, by FDP_ACC.1/DF, FTP_TRP.1/DF, FPT_TDC.1/DF.
FDP_ROL.1/DF	[FDP_ACC.1 Subset access control, or FDP_IFC.1 Subset information flow control]	Yes, by FDP_ACC.1/DF
FIA_UID.2/DF	No dependencies.	No dependency
FIA_UAU.2/DF	FIA_UID.1 Timing of identification	Yes, by FIA_UID.2/DF.
FIA_UAU.5/DF	No dependencies.	No dependency
FMT_MSA.1/DF	[FDP_ACC.1 Subset access control, or FDP_IFC.1 Subset information flow control], FMT_SMR.1 Security roles, FMT_SMF.1 Specification of Management Functions	Yes, by FDP_ACC.1/DF, FMT_SMR.1/DF, FMT_SMF.1/DF.
FMT_MSA.3/DF	FMT_MSA.1 Management of security attributes, FMT_SMR.1 Security roles	Yes, by FMT_MSA.1/DF, FMT_SMR.1/DF.

SFR	Dependency	Fulfilled in ST
FMT_MTD.1/DF	FMT_SMR.1 Security roles, FMT_SMF.1 Specification of Management Functions	Yes, by FMT_SMR.1/DF, FMT_SMF.1/DF.
FMT_SMF.1/DF	No dependencies.	No dependency
FMT_SMR.1/DF	FIA_UID.1 Timing of identification	Yes, by FIA_UID.2/DF.
FPR_UNL.1/DF	No dependencies.	No dependency
FPT_RPL.1/DF	No dependencies.	No dependency
FPT_TDC.1/DF	No dependencies.	No dependency
FTP_TRP.1/DF	No dependencies.	No dependency

### 6.3.3 Rationale for the Assurance Requirements

The selection of assurance components is based on the underlying Protection Profile. The Security Target uses the same augmentations as the Protection Profile, but chooses a higher assurance level. The level EAL5 is chosen in order to meet assurance expectations of access control applications and automatic fare collection systems. Additionally, the requirement of the Protection Profile to choose at least EAL4 is fulfilled.

The rationale for the augmentations is the same as in the Protection Profile. The assurance level EAL5 is an elaborated pre-defined level of the CC, part 3. The assurance components in an EAL level are chosen in a way that they build a mutually supportive and complete set of components. The requirements chosen for augmentation do not add any dependencies, which are not already fulfilled for the corresponding requirements contained in EAL5. Therefore, these components add additional assurance to EAL5, but the mutual support of the requirements is still guaranteed.

### 6.3.4 Security Requirements are Internally Consistent

The discussion of security functional requirements and assurance components in the preceding sections has shown that mutual support and consistency are given for both groups of requirements. The arguments given for the fact that the assurance components are adequate for the functionality of the TOE also show that the security functional and assurance requirements support each other and that there are no inconsistencies between these groups.

The security functional requirements required to meet the security objectives O.Leak-Inherent, O.Phys-Probing, O.Malfunction, O.Phys-Manipulation and O.Leak-Forced also protect the cryptographic algorithms and the access control function used to implement the Access Control Policy. The security objectives defined in the Protection Profile can be seen as "low-level protection" objectives, while the additional security objectives defined in this Security Target are "high-level protection" objectives. For example, O.Encryption states that the communication can be protected by encryption. While this ensures the rather high-level goal that the communication can not be eavesdropped, the overall goal that the communication is confidential is ensured with the help of the Protection Profile objective that prevent attacks on the key and the cryptographic implementation like probing or fault injection attacks.

## 7 TOE Summary Specification

### 7.1 Portions of the TOE Security Functionality

The TOE Security Functionality (TSF) directly corresponds to the TOE security functional requirements defined in Section 6. The table below lists the TSF of the TOE.

**Table 21. Portions of the TSF**

TSF portion	Title	Description
TSF.Service	Service functionality not related to DESFire functionality	This portion of the TSF comprises services like random number generation and provides mechanisms to store initialization, pre-personalization, and/or other data on the TOE.
TSF.Protection	General security measures to protect the TSF	This portion of the TSF comprises physical and logical protection to avoid information leakage and detect fault injection. It defines resets in case an error or attack was detected.
TSF.Control	Operating conditions, memory and hardware access control	This portion of the TSF controls the operating conditions.
TSF.DESFire	DESFire functionality	This portion of the TSF comprises all DESFire related security functionality such as cryptographic algorithms used by DESFire, implements the DESFire Access Control Policy and security functionality related to DESFire confidentiality, authentication, integrity and robustness.

The TSF are described in more detail in the following sections and the relation to the security functional requirements is shown.

### 7.2 TOE Summary Specification Rationale

#### 7.2.1 Mapping of Security Functional Requirements and TOE Security Functionality

SFR	TSF.Service	TSF.Protection	TSF.Control	TSF.DESFire	Description
Security Functional Requirements from the Protection Profile					
FRU_FLT.2			X		Limited fault tolerance
FPT_FLS.1			X		Failure with preservation of secure state
FMT_LIM.1			X		Limited capabilities



SFR	TSF.Service	TSF.Protection	TSF.Control	TSF.DESFire	Description
FMT_LIM.2			X		Limited availability
FAU_SAS.1	X				Audit storage
FDP_SDC.1		X			Stored data confidentiality
FDP_SDI.2		X			Stored data integrity monitoring and action
FPT_PHP.3		X			Resistance to physical attack
FDP_ITT.1		X			Basic internal transfer protection
FPT_ITT.1		X			Basic internal TSF data transfer protection
FDP_IFC.1		X			Subset information flow control
FCS_RNG.1/PTG2	X				Random number generation (Class PTG.2)
FCS_RNG.1/PTG3	X				Random number generation (Class PTG.3)
FCS_RNG.1/DRG4	X				Random number generation (Class DRG.4)
<b>Security Functional Requirements regarding Access Control</b>					
FDP_ACC.1/DF				X	Subset access control
FDP_ACF.1/DF				X	Security attribute based access control
FDP_ITC.2/DF				X	Import of user data with security attributes
FMT_MSA.1/DF				X	Management of security attributes
FMT_MSA.3/DF				X	Static attribute initialization
FMT_MTD.1/DF				X	Management of TSF data
FMT_SMF.1/DF				X	Specification of Management Functions
FMT_SMR.1/DF				X	Security roles
<b>Security Functional Requirements regarding Confidentiality, Authentication and Integrity</b>					
FCS_COP.1/DF-DES				X	Cryptographic Operation (DES)
FCS_COP.1/DF-AES				X	Cryptographic Operation (AES)
FCS_CKM.4/DF				X	Cryptographic key destruction
FIA_UAU.2/DF				X	User authentication before any action
FIA_UAU.5/DF				X	Multiple authentication mechanisms
FIA_UID.2/DF				X	User identification before any action
FPT_TDC.1/DF				X	Inter-TSF basic TSF data consistency
FTP_TRP.1/DF				X	Trusted path
<b>Security Functional Requirements regarding Robustness</b>					
FDP_ROL.1/DF				X	Basic rollback
FPR_UNL.1/DF				X	Unlinkability
FPT_RPL.1/DF				X	Replay detection

## 8 Bibliography

### 8.1 Evaluation documents

- [1] A proposal for: Functionality classes for random number generators, Wolfgang Killmann, T-Systems GEI GmbH, Werner Schindler, Bundesamt für Sicherheit in der Informationstechnik (BSI), Version 2.0, 18 September 2011.
- [2] Common Criteria for Information Technology Security Evaluation, Part 1: Introduction and general model, Version 3.1, Revision 5, CCMB-2017-04-001, April 2017.
- [3] Common Criteria for Information Technology Security Evaluation, Part 2: Security functional components, Version 3.1, Revision 5, CCMB-2017-04-002, April 2017.
- [4] Common Criteria for Information Technology Security Evaluation, Part 3: Security assurance components, Version 3.1, Revision 5, CCMB-2017-04-003, April 2017.
- [5] Common Methodology for Information Technology Security Evaluation, Evaluation methodology, Version 3.1, Revision 5, CCMB-2017-04-004, April 2017.
- [6] Security IC Platform Protection Profile with Augmentation Packages, Registered and Certified by Bundesamt für Sicherheit in der Informationstechnik (BSI) under the reference BSI-CC-PP-0084-2014, Version 1.0, 13 January 2014.

### 8.2 Developer documents

- [7] MF3Dx200Dpp(p)/02, MIFARE DESFire EV2 contactless smartcard IC, Objective data sheet, NXP Semiconductors, Revision 1.1, 17 January 2019.
- [8] MF3D92/MF3DA2, MIFARE DESFire EV2 16KB and 32KB contactless smartcard IC, Objective data sheet, NXP Semiconductors, Revision 1.1, 17 January 2019.
- [9] MF3Dx2 v2, Information on Guidance and Operation, Guidance and Operation Manual, NXP Semiconductors, Revision 1.3, 16 January 2019.

### 8.3 Standards

- [10] FIPS PUB 197: Advanced Encryption Standard (AES), Federal Information Processing Standards Publication 197, US Department of Commerce/National Institute of Standards and Technology, 26 November 2001.
- [11] NIST SP 800-38A: Recommendation for Block Cipher Modes of Operation: Methods and Techniques, Morris Dworkin, National Institute of Standards and Technology, December 2001.
- [12] NIST SP 800-38B: Recommendation for Block Cipher Modes of Operation: The CMAC Mode for Authentication, Morris Dworkin, National Institute of Standards and Technology, May 2005.
- [13] NIST SP 800-67, Recommendation for the Triple Data Encryption Algorithm (TDEA) Block Cipher, revised January 2012, National Institute of Standards and Technology.

## 9 Legal information

### 9.1 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

### 9.2 Disclaimers

**Limited warranty and liability** — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors. In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory. Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

**Right to make changes** — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification. Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products. NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or

the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

**Terms and conditions of commercial sale** — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. NXP Semiconductors hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of NXP Semiconductors products by customer.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

**Export control** — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

**Non-automotive qualified products** — Unless this data sheet expressly states that this specific NXP Semiconductors product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. NXP Semiconductors accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications. In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without NXP Semiconductors' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond NXP Semiconductors' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies NXP Semiconductors for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond NXP Semiconductors' standard warranty and NXP Semiconductors' product specifications.

**Translations** — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

### 9.3 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

**MIFARE** — is a trademark of NXP B.V.

**DESFire** — is a trademark of NXP B.V.

## Tables

Tab. 1.	TOE deliverables .....	4	Tab. 13.	Security Objectives for the Security IC Embedded Software (PP-0084) .....	15
Tab. 2.	Datasheet for 2, 4 and 8 KB memory sizes .....	4	Tab. 14.	Security Objectives for the Operational Environment (PP-0084) .....	16
Tab. 3.	Datasheet for 16 and 32 KB memory sizes .....	4	Tab. 15.	Additional security objectives for the operational environment defined in this Security Target .....	16
Tab. 4.	Available memory sizes .....	5	Tab. 16.	Security Problem Definition mapping to Security Objective .....	17
Tab. 5.	Threats defined in the Protection Profile (PP-0084) .....	10	Tab. 17.	Security Assurance Requirements .....	41
Tab. 6.	Additional threats defined in this Security Target .....	11	Tab. 18.	Security Functional Requirements mapping to Security Objectives .....	43
Tab. 7.	Organisational security policies defined in the Protection Profile (PP-0084) .....	11	Tab. 19.	Dependencies of Security Functional Requirements (PP-0084) .....	45
Tab. 8.	Additional organisational security policies defined in this Security Target .....	11	Tab. 20.	Dependencies of Security Functional Requirements (Security Target) .....	46
Tab. 9.	Assumptions defined in the Protection Profile (PP-0084) .....	12	Tab. 21.	Portions of the TSF .....	48
Tab. 10.	Additional assumptions defined in this Security Target .....	12			
Tab. 11.	Security Objectives of the TOE (PP-0084) .....	14			
Tab. 12.	Additional security objectives defined in this Security Target .....	14			

Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>	6.1.2.8	FMT_SMF.1/DF	35
1.1	ST Reference	3	6.1.2.9	FMT_SMR.1/DF	35
1.2	TOE Reference	3	6.1.2.10	Implications of the DESFire Access Control Policy	36
1.3	TOE Overview	3	6.1.3	Security Functional Requirements regarding Confidentiality, Authentication and Integrity	36
1.3.1	Required non-TOE Hardware/Software/Firmware	3	6.1.3.1	FCS_COP.1/DF-DES	36
1.4	TOE Description	3	6.1.3.2	FCS_COP.1/DF-AES	37
1.4.1	Physical Scope of the TOE	3	6.1.3.3	FCS_CKM.4/DF	37
1.4.1.1	Available Memory Sizes	4	6.1.3.4	FIA_UAU.2/DF	38
1.4.2	Logical Scope of the TOE	5	6.1.3.5	FIA_UAU.5/DF	38
1.4.2.1	Hardware Description	5	6.1.3.6	FIA_UID.2/DF	39
1.4.2.2	Software Description	5	6.1.3.7	FPT_TDC.1/DF	39
1.4.2.3	Documentation	6	6.1.3.8	FPT_TRP.1/DF	39
1.4.3	Life Cycle and Delivery of the TOE	6	6.1.4	Security Functional Requirements regarding Robustness	40
1.4.4	TOE Intended Usage	7	6.1.4.1	FDP_ROL.1/DF	40
1.4.5	Interface of the TOE	7	6.1.4.2	FPR_UNL.1/DF	41
<b>2</b>	<b>Conformance Claims</b>	<b>9</b>	6.1.4.3	FPT_RPL.1/DF	41
2.1	CC Conformance Claim	9	6.2	Security Assurance Requirements	41
2.2	PP Claim	9	6.2.1	Refinements of the TOE Security Assurance Requirements	42
2.3	Package Claim	9	6.2.1.1	Refinements Regarding ALC_CMS	42
2.4	Conformance Claim Rationale	9	6.2.1.2	Refinements regarding ADV_FSP	43
<b>3</b>	<b>Security Problem Definition</b>	<b>10</b>	6.3	Security Requirements Rationale	43
3.1	Description of Assets	10	6.3.1	Rationale for the Security Functional Requirements	43
3.2	Threats	10	6.3.2	Dependencies of Security Functional Requirements	45
3.3	Organisational Security Policies	11	6.3.3	Rationale for the Assurance Requirements	47
3.4	Assumptions	12	6.3.4	Security Requirements are Internally Consistent	47
<b>4</b>	<b>Security Objectives</b>	<b>14</b>	<b>7</b>	<b>TOE Summary Specification</b>	<b>48</b>
4.1	Security Objectives for the TOE	14	7.1	Portions of the TOE Security Functionality	48
4.2	Security Objectives for the Security IC Embedded Software	15	7.2	TOE Summary Specification Rationale	48
4.3	Security Objectives for the Operational Environment	15	7.2.1	Mapping of Security Functional Requirements and TOE Security Functionality	48
4.4	Security Objectives Rationale	16	<b>8</b>	<b>Bibliography</b>	<b>50</b>
<b>5</b>	<b>Extended Components Definition</b>	<b>20</b>	8.1	Evaluation documents	50
<b>6</b>	<b>Security Requirements</b>	<b>21</b>	8.2	Developer documents	50
6.1	Security Functional Requirements	21	8.3	Standards	50
6.1.1	Security Functional Requirements from the Protection Profile	21	<b>9</b>	<b>Legal information</b>	<b>51</b>
6.1.1.1	FAU_SAS.1	21			
6.1.1.2	FCS_RNG.1/PTG2	22			
6.1.1.3	FCS_RNG.1/PTG3	23			
6.1.1.4	FCS_RNG.1/DRG4	24			
6.1.1.5	FDP_SDC.1	25			
6.1.1.6	FDP_SDI.2	25			
6.1.2	Security Functional Requirements regarding Access Control	26			
6.1.2.1	DESFire Access Control Policy	26			
6.1.2.2	FDP_ACC.1/DF	30			
6.1.2.3	FDP_ACF.1/DF	31			
6.1.2.4	FDP_ITC.2/DF	32			
6.1.2.5	FMT_MSA.1/DF	33			
6.1.2.6	FMT_MSA.3/DF	33			
6.1.2.7	FMT_MTD.1/DF	34			

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.